

T-FAST® Wood screw JW2 wafer head



Cross references

Cordless screwdriver
 ASCM QSW
 Hexalobular bit TX
 Bit holder


Application range

- > Fastening of non-pre-drilled or pre-drilled components made of wood, wood-based material and pre-drilled and pre-set steel components to non-pre-drilled or pre-drilled components made of solid wood, solid structural timber (KVH), glued-laminated timber (BSH), laminated veneer lumber (LVL) in non-weathered areas.
- > Suitable for fastening over-rafter insulation systems
- > Ideal solution for fixing rafters onto purlins


Properties

- > Carbon steel with zinc-plated surface, 5 µm plating thickness and dry lubricant
- > Wafer head (STS) increases the pull-through capacity
- > The end mill at the transition to the non-threaded fastener shaft reduces the installation torque and simplifies the installation process
- > Partially threaded for tightening the components to be fastened
- > Optimised thread geometry for extremely fast processing
- > Special tip geometry ensures quick gripping and enables fast processing

Applications



Technical specifications



Certifications



JW2-ST5-6.0x80/48-V TX30

Hexalobular TX30
Zinc plated
Thread length [mm]
Screw length [mm]
External thread diameter [mm]
Wafer head with hexalobular TX and washer
Case-hardened steel
Wood screw
EJOT





Product online



Order description	d [mm]	l [mm]	l _g [mm]	d _n [mm]	Drive	PU [pieces]	Price/100 [EUR]	Article number	EAN
d 6.0									
T-FAST JW2-ST5-6x80/48-V TX30	6.0	80	48	14.0	TX30	250		3820000029	4061245073941
T-FAST JW2-ST5-6x100/60-V TX30	6.0	100	60	14.0	TX30	250		3820000030	4061245073958
T-FAST JW2-ST5-6x120/70-V TX30	6.0	120	70	14.0	TX30	250		3820000031	4061245073965
T-FAST JW2-ST5-6x140/70-V TX30	6.0	140	70	14.0	TX30	250		3820000032	4061245090414
T-FAST JW2-ST5-6x160/70-V TX30	6.0	160	70	14.0	TX30	100		3820000033	4061245073989
T-FAST JW2-ST5-6x180/70-V TX30	6.0	180	70	14.0	TX30	100		3820000034	4061245073996
T-FAST JW2-ST5-6x200/70-V TX30	6.0	200	70	14.0	TX30	100		3820000035	4061245074009
T-FAST JW2-ST5-6x220/70-V TX30	6.0	220	70	14.0	TX30	100		3820000036	4061245074016
T-FAST JW2-ST5-6x240/70-V TX30	6.0	240	70	14.0	TX30	100		3820000037	4061245074023
T-FAST JW2-ST5-6x260/70-V TX30	6.0	260	70	14.0	TX30	100		3820000038	4061245074030
T-FAST JW2-ST5-6x280/70-V TX30	6.0	280	70	14.0	TX30	100		3820000039	4061245074047
T-FAST JW2-ST5-6x300/70-V TX30	6.0	300	70	14.0	TX30	100		3820000040	4061245074054
d 8.0									
T-FAST JW2-ST5-8x80/48-V TX40	8.0	80	48	21.0	TX40	100		3820000041	4061245074115
T-FAST JW2-ST5-8x100/60-V TX40	8.0	100	60	21.0	TX40	100		3820000042	4061245070810
T-FAST JW2-ST5-8x120/80-V TX40	8.0	120	80	21.0	TX40	100		3820000043	4061245071619
T-FAST JW2-ST5-8x140/80-V TX40	8.0	140	80	21.0	TX40	100		3820000044	4061245070858
T-FAST JW2-ST5-8x160/80-V TX40	8.0	160	80	21.0	TX40	50		3820000045	4061245070865
T-FAST JW2-ST5-8x180/80-V TX40	8.0	180	80	21.0	TX40	50		3820000046	4061245070889
T-FAST JW2-ST5-8x200/80-V TX40	8.0	200	80	21.0	TX40	50		3820000047	4061245070896
T-FAST JW2-ST5-8x220/80-V TX40	8.0	220	80	21.0	TX40	50		3820000048	4061245071008
T-FAST JW2-ST5-8x240/80-V TX40	8.0	240	80	21.0	TX40	50		3820000049	4061245071015
T-FAST JW2-ST5-8x260/80-V TX40	8.0	260	80	21.0	TX40	50		3820000050	4061245071022
T-FAST JW2-ST5-8x280/80-V TX40	8.0	280	80	21.0	TX40	50		3820000051	4061245071039
T-FAST JW2-ST5-8x300/80-V TX40	8.0	300	80	21.0	TX40	50		3820000052	4061245071046
T-FAST JW2-ST5-8x320/80-V TX40	8.0	320	80	21.0	TX40	50		3820000053	4061245071053
T-FAST JW2-ST5-8x340/80-V TX40	8.0	340	80	21.0	TX40	50		3820000054	4061245074061
T-FAST JW2-ST5-8x360/80-V TX40	8.0	360	80	21.0	TX40	50		3820000055	4061245074078
T-FAST JW2-ST5-8x380/80-V TX40	8.0	380	80	21.0	TX40	50		3820000056	4061245074085
T-FAST JW2-ST5-8x400/80-V TX40	8.0	400	80	21.0	TX40	50		3820000057	4061245074092