DEKTITE® EZi-Seal Set

Application range

> For waterproofing pipes on corrugated metal or fibre cement roofs

Properties

> Version EDPM (black)
> Temperature resistance EPDM (black) permanent 50 °C to +115 °C, short-term up to +150 °C

Advantages

> Non-absorbent, closed-cell sealing surface
> Seals under compression even on wet surfaces
> Seals without use of a joint sealant through existing seal strip.
> No interference of thermal elongation of pipes
> No fatigue fractures
> 20-year warranty on material

Notice

Use folding blind rivets for fibre cement boards. Profile height max. 45 mm.

Included in delivery

1 pipe flashing
1 self-drilling screw set - optionally folding blind rivet set

Cross references

Joint sealant
Tightener
hose clamp

Assembly instruction

Product online

Order description	For pipe diameter [mm]	Base [mm]	Roof pitch [°]	Content screws [pieces]	Packaging unit [set]	Price/1 [EUR]	Article number	EAN
DFE 100 EZ Set	0–35	100 x 100	0–60	8	1		8200004706	4061245013947
DFE 101 EZ Set	5–55	139 x 139	0–35	8	1		8200104706	4061245013794
DFE 103 EZ Set	5–127	221 x 221	0–35	16	1		8200304706	4061245013770
DFE 104 EZ Set	75–175	280 x 280	0–35	20	1		8200404706	4061245013756
DFE 106 EZ Set	125–230	363 x 363	0–35	28	1		8200604706	4061245013732
DFE 107 EZ Set	150–300	456 x 456	0–35	32	1		8200704706	4061245013718
DFE 109 EZ Set	230–508	681 x 681	0–35	40	1		8200904706	4061245013695
Order information: Other dimensions upon request								

EJOT SE & Co. KG · Market Unit Construction · In der Stockwiese 35 · 57334 Bad Laasphe · Germany
T +49 2752 908-0 · F +49 2752 908-731 · construction@ejot.com · www.ejot.com/construction