

Window screw type S



Cross references

Bit cross recess H2

Application range

- > Fastening of tilt and turn fittings in regular and thin-walled PVC profiles and in steel or GRP inserts
- > Fixing locking plates, strips and bearings

Properties


- > Classic screw for fittings, technically leading, with double-start thread
- > The optimum also in thin-walled profiles
- > High stripping torques and pull-out values in PVC
- > Roll-sorted quality for automated fastening
- > Case-hardened steel
- > EJOSEAL is an inorganic, transparent sealant, to significantly increase the corrosion and heat resistance of fastening elements with zinc or zinc alloy coatings. EJOSEAL does not contain wax and is ideally suitable for direct fastening into plastic.

Processing information


- > Can also be fastened in steel, pre-drilling required (see chart)
- > Can also be fastened in GRP, pre-drilling might be required

Sheet thickness	Pre-drilling diameter
1.5 mm	3.0 mm
2.0 mm	3.2 mm
2.5 mm	3.5 mm

Technical specifications



Certifications



Product online



Order description	Length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
EJOSEAL					
Window screw S 4.2x13	13	1000		2225413607	4061245044637
Window screw S 4.2x16	16	1000		2225416607	4061245044644
Window screw S 4.2x20	20	1000		2225420607	4061245044651
Window screw S 4.2x22	22	1000		2225422607	4061245044668
Window screw S 4.2x25	25	1000		2225425607	4061245044675
Window screw S 4.2x30	30	1000		2225430607	4061245044682
Window screw S 4.2x35	35	1000		2225435607	4061245044699
Window screw S 4.2x40	40	1000		2225440607	4061245044705
Window screw S 4.2x45	45	1000		2225445607	4061245044712
Window screw S 4.2x55	55	1000		2225455607	4061245044729

Stainless steel available upon request

