

Concrete screw JBS-R-7.5



Application range

- > To fix roofing membranes and insulating material to concrete substructures
- > For combination with stress plate EcoTek 50


Properties

- > Case-hardened steel
- > Climadur-coated – high-quality coating to improve corrosion protection (15 Kesternich cycles, DIN 50018, 1997)

Applications



Technical specifications



Cross references

Stress plate EcoTek 50
 Bit extension
 Hammer drill SDS-plus
 Bit hexalobular TX30

Certifications



Product online



Order description	Length [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
JBS-R 7.5x80	80	100		2231080609	4061245020884
JBS-R 7.5x120	120	100		2231120609	4061245020877
JBS-R 7.5x150	150	100		2231150609	4061245020860
JBS-R 7.5x210	210	100		2231210609	4061245020853
JBS-R 7.5x300	300	100		2231300609	4061245062501

Compatibility acc. to ETA-07/0013

	HTV 82/40	HTE 82/40	HTV 82/40 TK	HTV 82/40 F	HTV 40 RU	HTK 2G 50xL	HTK 2G 75xL	EcoTek 50	EcoTek-T 50	HTK-S	Flat roof profile FP
JBS-R-7.5			X	X				X	X		X