

VSD 2G 8U Cavity Wall Repair Anchor



Application range

- > For subsequent securing of outer sheets to buildings
- > New: for subsequent securing of face bricks and vertically perforated clinkers
- > Cost-effective restoring of the structural integrity

Properties

- > Additional length 145 mm for subsequent securing of face bricks
- > Optimised expansion zone – now also for post-securing of vertically perforated clinkers
- > Universal expansion zone – secure installation in all substrates (A-C)
- > Double expansion wall anchor: simultaneous embedment in both the supporting wall and the outer sheet
- > The use of A4 stainless steel screws guarantees corrosion protection
- > With general building authorities approval
- > Clean and fast installation
- > Can be installed at 0°C


Cross references

- Cleaning brush
- Blow-out pump
- Tool belt
- Hammer drill SDS plus
- Cordless screwdriver ASCM
- Cordless hammer drill
- Bit hexalobular TX25
- Duster Expert SDS plus®

Note

The VSD cavity wall repair anchor enables the subsequent renovation of double-sheet masonry. Advanced corrosion or a complete lack of wire anchors can lead to decreased stability of the curtain wall and possibly cause considerable physical injury. In particular curtain walls made before 1979 should be subject to further inspection. When renovating the outer facade, the stability of the curtain wall must be verified. The EJOT® VSD is a particularly cost-effective solution for subsequent installation between load-bearing shell and curtain wall.

Technical specifications




Certifications



Base materials

- Suitable for load-bearing inner sheets made of
- > Concrete
 - > Solid brick
 - > Perforated brick and outer sheet of
 - > Solid clinker
 - > Vertically perforated clinker
 - > Face brick



Product online



Order description	Length l_d [mm]	Drill hole depth $t_s \leq$ [mm]	Distance a_2 [mm]	Curtain wall $h_a \geq$ [mm]	PU [pieces]	Price/100 [EUR]	Article number	EAN
Anchors with A4 stainless steel screws (-E)								
VSD-2G-8Ux145-E	145	155	–	60*	100		8502145600	4061245081939
VSD-2G-8Ux205-E	205	215	0–20	115	100		8502205600	4039161009771
VSD-2G-8Ux225-E	225	235	20–40	115	100		8502225600	4039161009788

*Face brick